

## **QUICK-ADAPTERS**

- for high pressure hoses and nozzle tubes with hydraulic coupler  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left$ 

Quick-adapter, short	· allows for the flexible combination with	length weight outer Ø	32 mm 45 g 20 mm	Connection Ref. No.:	
	various UMETA accessory parts			M 8 x 1 M 10 x 1 R 1/8	9907126 9907127 9907128
200/M 1	for button-head nipples M 1 (Ø 16) acc. to DIN 3404 button-head coupler made of aluminium	length height weight outer Ø	105 mm 28 mm 110 g 24 mm	<b>Type</b> 200/M 1	<b>Ref. No.:</b> 7321651
200/M 4	· for button-head nipples M 4 (Ø 10) acc. to DIN 3404 · button-head coupler made of steel	length height weight outer Ø	107 mm 28.5 mm 100 g 18 mm	<b>Type</b> 200/M 4	<b>Ref. No.:</b> 7321851
200/M 22	· for button-head nipples M 22 (Ø 22) acc. to DIN 3404 · button-head coupler made of aluminium	length height weight outer Ø	114 mm 38.5 mm 160 g 32 mm	<b>Type</b> 200/M 22	<b>Ref. No.:</b> 7321751
200/K	· for cardan shafts, with hollow nozzle	length weight	133 mm 80 g	<b>Type</b> 200/K	Ref. No.: 7322451
200/S	∙ for flush-type nipples acc. to DIN 3405	length weight	92 mm 65 g	<b>Type</b> 200/S	<b>Ref. No.:</b> 7321151
200/XS	· hard to reach areas, for cardan shafts and smallest nipples of any kind	length weight pin point tul outer Ø inner Ø length	95 mm 60 g be 4 mm 0.8 mm 55 mm	Type 200/XS	<b>Ref. No.:</b> 7321551
Quick-adapters in a handy carrying case		consisting each 1 x	of: 200/M 1 200/M 4 200/M 22 200/K 200/S 200/XS swivel joint		Ref. No.: 9230004